

TL-D400S

Baie de lecteur	4 x SATA 6 Gbits/s, 3 Gbits/s 3,5 pouces
Audio Alert On/Off Switch	Yes
Facteur de forme	Tour
Interface hôte	1 x SFF-8088
Témoins lumineux	HDD 1 à 4, État, Lien, Erreur du ventilateur
Boutons	Interrupteur d'alimentation
Poids (net)	3.66 kg
Nombre max. de HDD/SSD pris en charge	4 x SATA 6 Gbits/s 3,5 pouces
Type de disque dur	Lecteurs de disque dur SATA 3,5 pouces Lecteurs de disque dur SATA 2,5 pouces Lecteurs SSD SATA 2,5 pouces
Température de fonctionnement	0 - 40 °C (32°F - 104°F)
Humidité relative	HR 5~95% sans condensation RH, WBGT : 27˚C (80,6˚F)
Unité d'alimentation	Adaptateur 65W, 100 – 240 V
Consommation électrique : Mode de fonctionnement, typique	22,985 W
Fan Mode Switch	Yes (Auto, élevé, moyen, faible)
Ventilateur	1 x 120 mm, 12 V CC
Niveau sonore	20,1 db(A)
Avertissement système	Buzzer
Emplacement de sécurité Kensington	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.
Designs and specifications are subject to change without notice.