

| TL-R1200C-RP | |
|---|---|
| Audio Alert On/Off Switch | Yes |
| Facteur de forme | 2 unités montées en rack |
| Interface hôte | 1 x USB 3.2 Gen 2 Type-C |
| Témoins lumineux | HDD 1 à 12, État, Lien, Erreur du ventilateur |
| Boutons | Interrupteur d'alimentation |
| Dimensions (H x L x P) | 88,6 × 482 × 562,5 mm |
| Poids (net) | 11.03 kg |
| Poids (brut) | 14.29 kg |
| Nombre max. de HDD/SSD pris en charge | 12 x SATA 6 Gbits/s 3,5 pouces |
| Type de disque dur | Lecteurs de disque dur SATA 3,5 pouces<br>Lecteurs de disque dur SATA 2,5 pouces<br>Lecteurs SSD SATA 2,5 pouces |
| Température de fonctionnement | 0 - 40 °C (32°F - 104°F) |
| Humidité relative | HR 5~95% sans condensation RH, WBGT : 27˚C (80,6˚F) |
| Unité d'alimentation | Bloc d'alimentation 250 W, 100 – 240 V |
| Consommation électrique : Mode de fonctionnement, typique | 82,26 W |
| Fan Mode Switch | Yes (Auto, élevé, moyen, faible) |
| Ventilateur | 2 x 70mm, 12 V CC |
| Niveau sonore | 33,4 db(A) |
| Avertissement système | Buzzer |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front

of operating NAS.
Designs and specifications are subject to change without notice.