

TS-133

CPU	ARM 4-core Cortex-A55 1.8GHz processor
CPU Architecture	64-bit ARM
Floating Point Unit	Yes
Encryption Engine	Yes
System Memory	2 GB on board (non-expandable)
Maximum Memory	2 GB on board (non-expandable)
Flash Memory	4 GB (Dual boot OS protection)
Drive Bay	1 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Gigabit Ethernet Port (RJ45)	1
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
USB 2.0 port	1
USB 3.2 Gen 1 port	1
Form Factor	Tower
LED Indicators	System Status, LAN, HDD
Buttons	Power, Reset
Dimensions (HxWxD)	7.38 × 2.6 × 6.2 inch
Weight (Net)	1.34 lbs
Weight (Gross)	2.8 lbs
Operating Temperature	0 - 40 °C (32°F - 104°F)

Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27˚C (80.6˚F)
Power Supply Unit	36W Adapter, 100-240V
Power Consumption: HDD Sleep Mode	2.74 W
Power Consumption: Operating Mode, Typical	7.32 W
Fan	1 x 50mm, 12VDC
System Warning	Buzzer
Standard Warranty	2
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	200

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.
Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.
The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.
Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.
Designs and specifications are subject to change without notice.